

1120TST9

FOUNDATION RIG WITH EXTENDABLE UNDERCARRIAGE




qmatec

MACHINE

| | |
|------------------|-------------------------|
| Engine Model | Deutz TCD 6.1 L6 Tier 5 |
| Engine Power | 180 kW |
| Tractive Power | 33 000 Nm |
| Track Width | 500 mm |
| Weight std. from | 23 000 kg |

MAST

| | |
|-------------------|------------|
| Feed Stroke | 10 000 mm |
| Retract Force | 20 000 kg |
| Mast Winch | 750 kg |
| Drill Table | Ø420 mm |
| Mast Displacement | 1500 mm |
| Rapid Feed | 0,70 m/sec |
| Rapid Pull up | 0,60 m/sec |

ROTATION HEAD

| | |
|-----------------|--------------------------------|
| Torque | Alt. 1: 4 200 / 8 400 Nm |
| | Alt. 2: 5 600 / 11 200 Nm |
| Rotation Speed | Alt 1. 0-70 / 0-35 rpm |
| | Alt 2. 0-100 / 0-50 rpm |
| Spindle Threads | API 2 7/8" IF - API 2 3/8" REG |

OTHER

| | |
|-----------------------|----------------|
| Oscillation on Tracks | +/- 15 deg. |
| Track Speed | 2,5 / 4,0 km/h |
| Battery | 2 x 75 Ah |
| Hyd. Tank | 430 L |

SELECTION OF OPTIONAL EQUIPMENT

Main Winch 6700 kg

Break-Out Clamps

Welding Machine/Generator and Water Pumps

Water Tanks / Tool Cabinets

Hose drums/bottle stand

Crane 2.7 tm, Radio Operated

Digital Inclinator w/Display on Radio

Lubrication System

Other Equipment Delivered acc. to Agreement

