

QMATEC 1114TS

FOUNDATION RIG



QMATEC 1114 TS Technical Data

MACHINE

Diesel Engine	Deutz TCD 6.1 Stage V
Power	180 kW
Tractive power	25 000 kg
Track width	500 mm
Speed track	2,5 / 4,0 km/h
Oscillation	+15, -15 gr
Weight std. type from	15 000 kg

FEEDER

Feed length	4 000 mm
Feeder force	6 000 kg
Pull up	14 000 kg
Mast winch	750 kg
Drill table	Ø520 mm
Feed Extention	1 500 mm
Rapid feed	0,30 m/sec
Rapid pull up	0,30 m/sec
Pipe wrench cylinder	Ø 90 mm

ROTATION UNIT

Torque	8000/16000 Nm
Rotation speed	0-75 / 0-37 rpm
Spindel thread API 2	API2 - 7/8"IF

OTHER

Battery	2 x 50 Ah dry
Hydr. tank	430 L
Diesel Tank	360 L

OPTIONAL EQUIPMENT

Main winch 6000 kg.
 Welding machine
 Different types of water pumps and water tanks
 Diverter housing
 Pipe rack
 Crane 2,7 tm alt. 4 tm, radiocontrolled
 Other equipment delivered acc. to agreement

